



NOTE  
 MATERIAL  
 NOTE:  
 HOUSING:PBT+30%GF,UL94V-0.  
 SHELL:SPCC.  
 CONTACT:PHOSPHOR BRONZE  
 CONTACT PLATE WITH GOLD PLATE 15U"  
 SHELL:NICKEL OVER ALL PLATING  
 DIELECTRIC WITHSTANDING VOLTAGE:100V(AC)  
 CONTACT RESISTANCE:50M $\Omega$  MAX  
 INSULATION RESISTANCE:100M $\Omega$  MIN  
 DIELECTRIC WITHSTANDING VOLTAGE:100V(AC).  
 CONTACT RESISTANCE:50M $\Omega$  MAX  
 INSULATION RESISTANCE:100M $\Omega$  MIN  
 OPERATING TEMPERATURE: -55°C~105°C.  
 PART NO. DESCRIPTION:

12 1-09 1 5 N X XX 02  
 PLATING GOLD: \_\_\_\_\_ STANDARD  
 A=1u" B=3u" \_\_\_\_\_ HOUSING COLOR:  
 C=5u" D=10u" \_\_\_\_\_  
 E=15u" F=30u" O=0.5u" 05=BLUE -----

10/05/22	ING		NEW DWG		AO
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表			 		
			TITLE: USB 3.0 B TYPE公頭焊線三件式 (極佳)		
X.X	$\pm 0.30$	X.X"	$\pm 3.00$ "	APPD:	PRODUCT NO: 121-0915NE0502
X.XX	$\pm 0.20$	X.XX"	$\pm 1.00$ "	CHECK:	DATE SCALE UNIT TYPE PAGE
X.XXX	$\pm 0.10$	X.XXX"	$\pm 0.05$ "	DRAW:	2010.05.22 1:1 mm Z 1/1